

2010

Escape Velocity

Nikola Vlacic
University of South Florida

Advisors:

Masahiko Saito, Mathematics and Statistics
Scott Campbell, Chemical & Biomedical Engineering
Carlos Smith, Chemical & Biomedical Engineering

Problem Suggested By: Scott Campbell

Follow this and additional works at: <https://scholarcommons.usf.edu/ujmm>



Part of the [Mathematics Commons](#)

UJMM is an open access journal, free to authors and readers, and relies on your support:

[Donate Now](#)

Recommended Citation

Vlacic, Nikola (2010) "Escape Velocity," *Undergraduate Journal of Mathematical Modeling: One + Two*: Vol. 3: Iss. 1, Article 12.

DOI: <http://dx.doi.org/10.5038/2326-3652.3.1.24>

Available at: <https://scholarcommons.usf.edu/ujmm/vol3/iss1/24>

Escape Velocity

Abstract

In this project, we investigated if it is feasible for a single staged rocket with constant thrust to attain escape velocity. We derived an equation for the velocity and position of a single staged rocket that launches vertically. From this equation, we determined if an ideal model of a rocket is able to reach escape velocity.

Keywords

Escape Velocity, Single Staged Rocket, Kinetic Energy

Creative Commons License



This work is licensed under a [Creative Commons Attribution-Noncommercial-Share Alike 4.0 License](https://creativecommons.org/licenses/by-nc-sa/4.0/).

Erratum

This article was previously called Article 24.

TABLE OF CONTENTS

Problem Statement.....	3
Motivation.....	3
Mathematical Description and Solution Approach	3
Discussion.....	5
Conclusion and Recommendations.....	6
Nomenclature.....	7
References.....	7

PROBLEM STATEMENT

The objective of this project is to determine the velocity needed for a single staged rocket to leave Earth's gravity and how much fuel would be required.

We ignore the effects of the Earth's rotation and assume that the rocket only travels vertically in order to simplify the calculations. Additionally, we ignore the drag forces since rockets tend to be very massive and they quickly ascend to heights where the air resistance becomes negligible. Therefore, the only forces which we shall take into account are thrust and gravity. Throughout this project we shall assume that the rocket is a single staged rocket. The Saturn V rocket and the Space Shuttle are multi-staged rockets that discard their fuel tanks and rocket engines once their fuel is consumed.

MOTIVATION

Understanding the requirements for achieving escape velocity can give engineers and scientists a starting point for more complex problems. For instance, it is necessary for a rocket to attain escape velocity in order for the rocket to reach the moon or for the rocket to reach the depths of the solar system.

MATHEMATICAL DESCRIPTION AND SOLUTION APPROACH

In this problem, we shall let t denote the time after the rocket launches. We also let $y(t)$ denote the height of the rocket above earth's surface at time t . Recall that the only forces that we consider acting on the rocket are thrust and gravity. Since acceleration is the second derivative of position, we have

$$F_t - F_g = F = m a = m(t) \frac{d^2 y(t)}{dt^2}$$

where F_t and F_g are the forces of thrust and gravity and $m(t)$ is the mass of the rocket at time t .

The law of universal gravitation states that

$$F_g = G_c \frac{m_e m(t)}{(r + y(t))^2}$$

where G_c is the universal gravitational constant, m_e is the mass of the Earth, $m(t)$ is the mass of the rocket, t is the time after launch, and r is the radius of the Earth. We also have

$$m(t) = R + F - Ct$$

where R is the mass of the rocket without fuel, F is the mass of the initial fuel load, and C is the rate of fuel consumption. We shall assume that the fuel burns at a constant rate and the thrust is constant. By substituting the functions $m(t)$ and F_g we get

$$F_t - G_c \frac{m_e(R+F-Ct)}{(r+y(t))^2} = (R + F - Ct) \frac{d^2 y(t)}{dt^2} \quad (1)$$

therefore

$$\frac{d^2 y}{dt^2} = \frac{F_t}{(R+F-Ct)} - G_c \frac{m_e}{(r+y(t))^2}. \quad (2)$$

For an object to have enough speed to leave the gravitational pull of the Earth, the object's kinetic energy must be great enough to lift the object to outer space. The energy required to lift the rocket from height y into space is the integral

$$\int_y^\infty G_c \frac{m_e m}{(r+z)^2} dz = G_c m_e m \frac{1}{r+y}. \quad (3)$$

Therefore, in order to have more kinetic energy than potential energy, we must have

$$\frac{1}{2} m \left(\frac{dy}{dt} \right)^2 \geq G_c m_e m \frac{1}{r+y} \quad (4)$$

In other words, if t_f is the time that the rocket runs out of fuel and V_f is the velocity when the rocket runs out of fuel, then in order to have enough kinetic energy to escape Earth's gravitational field we must have

$$V_f \geq \sqrt{\frac{2G_c m_e}{r+y(t_f)}}. \quad (5)$$

DISCUSSION

We shall now compute whether it is reasonable for a single staged rocket to achieve escape velocity. The velocity 4,500 m/s is near the theoretical maximum exhaust velocity for chemical rockets that burn fuel, and it is nearly impossible to have a rocket that is 90% fuel (Turner. 16-17). Furthermore, since chemical rockets have very high thrust to weight ratios compared to all other propulsion systems, chemical rockets are the only feasible rocket systems capable of reaching escape velocity (Sutton. 30). We shall therefore assume that we have a rocket where the mass of the rocket with fuel is $4 \times 10^6 kg$, and the mass of the rocket without fuel is $5 \times 10^5 kg$. Furthermore, assume that the average exhaust velocity is 4,000 m/s and the rocket burns $2 \times 10^4 kg$ of fuel per second. With these optimal specifications, the rocket produces $8 \times 10^7 N$ of thrust, and the engine burns for 175 s. By solving the differential equation (2) numerically, we conclude that the rocket achieves a velocity of 6,649.18m/s at 343 km above the earth's surface after 175 s. On the other hand, the escape velocity at 343 km above earth's surface is 1,0896m/s. This rocket did not reach escape velocity. Furthermore, the air resistance further hinders the rocket's ability to reach escape velocity. In addition to the problem of not being able to reach escape velocity, there are other problems with this rocket model. In this model, the rocket exerts 16 times the force of gravity after 175 s while at launch

the rocket only exerts two times the force of gravity. This acceleration will produce a great amount of stress on the rocket and will not be bearable for any passengers inside the rocket.

CONCLUSION AND RECOMMENDATIONS

We conclude that it is not reasonable for a single staged rocket of constant thrust to escape Earth's gravitational field when launched vertically. In order for a chemically based rocket to reach escape velocity, it is necessary for the rocket to discard excess fuel tanks and engines.

NOMENCLATURE

Symbol	Description	Units
t	Time after launch	Seconds (s)
$y(t)$	Height of rocket	Meters (m)
F_t	Force of thrust	Newtons (N)
F_g	Force of gravity	N
$m(t)$	Mass of Rocket	Kilograms (kg)
R	Mass of rocket without fuel	kg
F	Mass of fuel	kg
C	Rate of fuel consumption	kg/s
G_c	Universal gravitational constant	$N(m/kg)^2$
m_e	Mass of earth	kg
R	Radius of earth	m
t_f	Length of engine burn	s
V_f	Final velocity	m/s

REFERENCES

George P. Sutton. Rocket Propulsion Elements. New York: Wiley-Interscience, 1986.

Martin J. L. Turner. Rocket and Spacecraft Propulsion. Chichester, UK:
Praxis Publishing Ltd., 2000.